

LINITOP®

ACRYL PARKET

Water-based floor varnish Special "normal to intense usage"



INTERIOR



Priority to wood

Description	Water based, single component polyurethane colourless floor varnish. Protects indoor wood subject to abrasion while preserving its natural colour.
Classification	Family 1 - Class 6a/7b2 (according to classifications NBT 22-003 and NFT 36-005).
Properties	<ul style="list-style-type: none"> • Protects and waterproofs the wood. Enhances the woods natural beauty. • High resistance to abrasion, scratches, water splashes and marks. Ideal for bathrooms. • Withstands chemical products including ammoniated ones. • Dries and hardens rapidly. Odourless. • Non-slip. Easily washed. Does not yellow. • Satin appearance. Can be coloured (consult us). • Ecological formula of the latest generation: less than 5% VOC.
Basic uses	<ul style="list-style-type: none"> • Indoors. • Normal to intense usage. • Parquet, stairs, floors, work surfaces, etc. • Can be used on all wood types normally used for this type of structure.
Characteristics <ul style="list-style-type: none"> • Composition: • Density (at +20°C): • Flash point: • Viscosity: • Solid content: • VOC: • Packaging: • Shelf life: • Storage conditions: • Appearance in the can: • Appearance of the dry product: • Colour: • Tools: • Dilution: • Cleaning of the tools: • Conditions of application: • Coverage: • Drying (data at +20°C and 50% relative humidity): • Safety: 	Modified polyurethane acrylic resins. 1.045 ± 0.05. Not classified as inflammable. Semi-fluid liquid. 40% ± 2. EU limit value for this product (cat A/e): 130 g/l (2010). This product contains a maximum of 50 g/l VOC. 0.75 l and 2.5 l. At least 2 years in the unused closed original packaging. Keep away from frost and high temperatures. Milky liquid. Satin/matt. Colourless. Brush, microfibre roller. Ready to use. Water. Do not apply at an ambient temperature of less than +10°C or greater than +25°C. 10 to 12 m ² /l. - Dust-dry: 1h. - Recoatable: 4h. - Final hardness: 2 weeks. Refer to the safety data sheet and the text given on the packaging, in accordance with the applicable legislation.

PRIORITY TO WOOD

Surface preparation

- Use on wood whose usage, nature, quality, treatments and preparation comply with the applicable standards and DTU (DTU 59.1).
 - The inspection and preparation of the surface are the responsibility of the user.
 - The wood must be dry, clean, sound, and prepared (degrease, sand, clean according to the standard practices for this type of work). The preparation of the surface is essential for an optimum finish.
- New wood:**
- Prepare the surface (sand with coarse and medium grade according to the condition of the surface), then finish with finishing sandpaper according to standard practices.
- Respect the applicable grading scale during sanding.
- Old floor varnish in a good condition:**
- Roughen the entire surface to enable better adhesion.
- Damaged floor varnish:**
- Make the entire surface bare by sanding or stripping (consult us).
- Surfaces formerly oiled or polished:**
- Preferably dry strip followed by degreasing then finishing sanding (consult us).
- In all cases comply with the applicable standards and DTU.
- NB:** After sanding, always clean the surface carefully with a vacuum cleaner. Do not forget the dust traps (pipes, radiators...).

Recommendations before application

- Ready for use. Do not dilute. Shake the product well before and during application.
- Do not apply at an ambient air and wood temperature of less than +10°C and greater than +25°C. A relative humidity of 50% enables optimum drying.
- The moisture of the wood must not be greater than 12% according to the applicable DTU.
- Protect everything that does not have to be treated.
- Work in a well ventilated area.
- Switch off the underfloor heating.

Directions for use

- According to the condition of the surface:
- New wood or made bare. Prepared surface:**
- Apply a first even generous coat of Acryl Parket.
 - Allow to dry for 4 hours between coats depending on the ambient conditions.
 - Sand (grit 280) then clean meticulously.
 - Apply a second coat.
 - Do not exceed 24 hours between the application of 2 coats.
- Old floor varnish in a good condition:**
- Refer to the "surface preparation" section then apply Acryl Parket according to the above instructions.
- Old damaged floor varnish:**
- Make the surface bare by sanding according to standard practices then apply Acryl Parket according to the above procedure.
- Make the surface bare by stripping:** consult us.
- NB:** Always clean very meticulously after sanding or stripping.

Advice of the professionals

- Good surface preparation is essential for the final appearance of the finish.
- Depending on the condition of the surface several sanding stages will be required: from grit 40 to 180. It is advisable to only use one grade at a time.
- **For a perfect result:**
- Apply Acryl Parket in the direction of the wood grain. Do 3 criss-cross passes in one application by facing the light and starting at the part opposite the door so as to progress towards it.
- Start with the edges and then do the entire surface by working in zones of 2 metres by 2 metres.
- Do not open the windows during application to avoid drying too quickly.
- **Coloured base before finish:**
- Apply a coat of Acryl Prim*. After drying and without sanding, finish with two coats of Acryl Parket, sanding between these two coats.
- **Precautions:**
- Do not cover the sealed surface with carpets or protective covers for 14 days after the application of the floor varnish.
- Wait at least 48 hours before putting back furniture, protecting the legs with pads.
- Light usage (with care): 24/48h.
- Normal usage: 7 days.
- Intense usage: 15 days.

Maintenance

- Regularly dust the sealed surface with a brush or vacuum cleaner.
- Clean the surface with a gentle soap compatible with a floor varnish.
- If grease and other dirt accumulate that foul the surface over time, use a powerful cleaner. Do not use this type of product in the first 3 weeks following the application of Acryl Parket (consult us).

* same manufacturer

For further help or advice please contact us on:
Belgium: +32 (0)10 420090 - 0800 95549
France: +33 (0)1 60 86 48 70
or consult our site: www.linitop.com

This notice cancels and replaces all previous notices on the same product. The advice provided, in particular on the maintenance, is only indicative and cannot substitute for an appropriate description of the nature and condition of the surface to be worked on. With technical developments continually occurring, it is for our customers to check, before application, with our services that this notice has not been replaced by a more recent edition.

LINITOP® is a trademark



Durieu S.A.
91070 BONDOUFLE - France
 T. +33 (0)1 60 86 48 70
 F. +33 (0)1 60 86 84 84
info@durieu.com
www.durieu.com

Durieu Coatings S.A. / N.V.
New Tech Center
Avenue Albert Einstein 2 A
1348 Louvain-La-Neuve
Belgique / België
 T. +32 (0)10 420 090
 F. +32 (0)10 420 099
info@durieucoatings.com
www.durieucoatings.com

0800 95 549