

# LINITOP®

## LINITOP CLASSIC ACRYL

### Decorative woodstain



INTERIOR  
EXTERIOR

Priority to wood

<b>Description</b>	High performance, satin finish, waterborne woodstain that gives long lasting protection.
<b>Classification</b>	Family 1 - Class 4a/7B2 (according to classifications NBT 22-003 and NFT 36-005).
<b>Properties</b>	<ul style="list-style-type: none"> <li>• Non drip for easy application and a perfect finish.</li> <li>• Excellent resistance to blocking.</li> <li>• Microporous - water repellent.</li> <li>• Transparent: Enhances the wood and maintains its natural appearance.</li> <li>• Highly flexible film, limits the risks of flaking.</li> <li>• Special anti-UV pigmentation for optimum protection.</li> <li>• Excellent resistance to bad weather.</li> </ul>
<b>Basic uses</b>	<ul style="list-style-type: none"> <li>• Indoor and outdoor vertical surfaces.</li> <li>• Protects and decorates wooden doors, door and window frames, beams, panelling,...</li> </ul>
<b>Characteristics</b>	<ul style="list-style-type: none"> <li>• <b>Composition:</b> Acrylic resins and vegetable oil.</li> <li>• <b>Density (at +20°C):</b> 1.03 ± 0.05.</li> <li>• <b>Flash point:</b> Classified as non-flammable.</li> <li>• <b>Viscosity:</b> Gel.</li> <li>• <b>Solid content:</b> 38% ± 2.</li> <li>• <b>VOC:</b> EU limit value for this product (cat A/e): 130 g/l (2010). This product contains a maximum of 99 g/l VOC.</li> <li>• <b>Packaging:</b> 1 l - 5 l.</li> <li>• <b>Shelf life:</b> At least 1 year in the unused closed original packaging.</li> <li>• <b>Storage conditions:</b> Keep away from frost and high temperatures.</li> <li>• <b>Appearance in the can:</b> Viscous liquid.</li> <li>• <b>Appearance of the dry product:</b></li> <li>• <b>Colours:</b> <p>Satin.</p> </li> <li>• <b>Tools:</b> Brush, roller, spray gun.</li> <li>• <b>Dilution:</b> Ready to use.</li> <li>• <b>Cleaning of the tools:</b> Water.</li> <li>• <b>Conditions of application:</b> Respect the conditions and instructions stipulated by the manufacturer. Do not apply at an ambient temperature of less than +10°C or greater than +30°C. Relative humidity: 50%.</li> <li>• <b>Coverage:</b> ± 14 m²/l.</li> <li>• <b>Drying (data at +20°C and 50% relative humidity):</b> <ul style="list-style-type: none"> <li>- Dust-dry: 2 h.</li> <li>- Recoatable: 6 h.</li> </ul> </li> <li>• <b>Safety:</b> Refer to the safety data sheet and the text given on the packaging, in accordance with the applicable legislation.</li> </ul>

Priority to wood

## Surface preparation

- Use on wood whose usage, nature, quality, treatments and preparation comply with the applicable standards and DTU (DTU 59.1).
  - The inspection and preparation of the surface are the responsibility of the user.
  - The wood must be dry, clean, in sound condition, free of millglaze and properly prepared (degrease, sand, dust off).
  - On new wood:**
    - Sand (grit 120) to encourage and optimise the opening of the pores.
  - Use on already stained wood is possible provided that the existing woodstain is in a good condition. However, the entire surface will have to be meticulously sanded (grit 220).
  - On old wood, where the existing woodstain is in a poor condition:**
    - Remove existing finish back to bare wood by sanding or stripping.
- NB:** After sanding, always carefully dust the surface.

## Recommendations before application

- Ready to use. Shake well before application.
  - Do not apply at an ambient air and wood temperature of less than +10°C and greater than +30°C. Optimum drying achieved at a relative humidity of 50%.
  - Comply with the applicable standards and DTU.
  - Protect everything that does not have to be treated.
  - The moisture of the wood must not be greater than 15%.
- NB:** To protect the wood against UV, do not use «colourless» by itself outside as the finish coat. Always finish with 2 coloured coats.

## Directions for use

- According to the condition of the surface:
- New wood or restored to new after stripping or sanding:**
- Apply a coat of LINITOP PRIM & FINISH or ACRYL PRIM\*\*.
  - After fully drying, finish with two coats of LINITOP CLASSIC ACRYL\*.
- Greyed wood:**
- Clean with WOOD CLEANER\*\*.
  - Sand (grit 120) if necessary.
  - On a clean and dry surface, apply a coat of LINITOP PRIM & FINISH or ACRYL PRIM\*\* finish with two coats of LINITOP CLASSIC ACRYL\*.
- Darkened oiled wood:**
- Remove the oil with the WOOD OIL CLEANER\*\* and WOOD CLEANER\*\* system.
  - Sand (grit 120) if necessary.
  - On a clean and dry surface, apply a coat of LINITOP PRIM & FINISH or ACRYL PRIM\*\* finish with two coats of LINITOP CLASSIC ACRYL\*.
- Wood to be stripped:** consult us.
- Indoors, all woods:**
- **Softwoods (resinous):**
    - Apply 2 to 3 coats of LINITOP CLASSIC ACRYL.
  - **Hardwoods:**
    - Apply 1 to 2 coats of LINITOP CLASSIC ACRYL.
- NB:** An additional coat may be required depending on the absorption of the wood and the desired appearance.

## Advice of the professionals

- Always apply LINITOP CLASSIC ACRYL in the direction of the grain.
- On new or stripped wood that is not durable and has not been treated with a preservative, it is recommended to first treat the wood with an insecticide, fungicide and anti-blue stain agent. Consult us.
- During application, pay particular attention to grooves and end grains.
- When working with a spray gun, smooth with a brush to avoid any running and to aid the penetration of the product.

## Maintenance

- Usual restoration:**
- Apply one or two coats of LINITOP CLASSIC ACRYL\* according to the condition of the coating and after cleaning and sanding.
- Restoration on a highly damaged surface:**
- Remove existing finish back to bare wood by sanding or stripping. Apply a coat of LINITOP PRIM & FINISH or ACRYL PRIM\*\* finish with 2 coats of LINITOP CLASSIC ACRYL\*.
- NB:** After sanding, always carefully dust the surface.

\* To protect the wood against UV, do not use «colourless» by itself outside as the finish coat. Always finish with 2 coloured coats.  
 \*\* Same manufacturer

**For further help or advice please contact us on:**  
**Belgium: +32 (0)10 420090 - 0800 95549**  
**France: +33 (0)1 60 86 48 70**  
**or consult our site: [www.linitop.com](http://www.linitop.com)**

This notice cancels and replaces all previous notices on the same product. The advice provided, in particular on the maintenance, is only indicative and cannot substitute for an appropriate description of the nature and condition of the surface to be worked on. With technical developments continually occurring, it is for our customers to check, before application, with our services that this notice has not been replaced by a more recent edition.

LINITOP® is a trademark



**Durieu S.A.**  
 91070 BONDOUFLE - France  
 T. +33 (0)1 60 86 48 70  
 F. +33 (0)1 60 86 84 84  
 info@durieu.com  
 www.durieu.com

**Durieu Coatings S.A. / N.V.**  
 New Tech Center  
 Avenue Albert Einstein 2 A  
 1348 Louvain-La-Neuve  
 Belgique / België  
 T. +32 (0)10 420 090  
 F. +32 (0)10 420 099  
 info@durieucoatings.com  
 www.durieucoatings.com

**0800 95 549**