LINITOP

WOOD CLEANER







Restores greyed wood to its original appearance.

Also cleans cement stained by rust, discoloured stone and plastic.

Removes marks linked to bad weather, mould, rust...

Returns the shine to plastics that have become porous under the action of UV.

Properties

Gelified water-based cleaner.

Cleans and restores unfinished wood to its original colour.

Neutral - will not damage the surface.

Non aggressive - harmless to plants and shrubs.

Biodegradable - solvent free (can be rinsed with water).

Basic uses

- All greyed or dirty outdoor woods (resinous wood, pressure treated or otherwise, tropical hardwoods, thermo-heated wood, broadleaved wood...) not protected by linseed or teak oils.
- Effective on all surfaces: terraces, duckboards, weatherboarding, chalets, boat decks, garden furniture...
- Other surfaces: cement stained by rust, discoloured stone, powdery plastic.
- Also used as a neutraliser on wood after using Wood Oil Cleaner*.

Characteristics

Composition:

• Density (at +20°C):

• Flash point:

Packaging:

• Shelf life:

Storage conditions:

• Appearance in the can:

• Tools:

Dilution:

Cleaning of the tools:

• Conditions of application:

Coverage:

• Drying (data at +20°C and

Oxalic acid - water.

 1.050 ± 0.25 .

Not classified as inflammable.

1 I - 2.5 I.

At least 2 years in the closed original packaging.

Keep away from frost and high temperatures.

Gelified liquid.

Synthetic brush or roller (long hair). Nylon brush with hard bristles.

Do not dilute. Ready to use.

Water + detergent.

Do not apply at an ambient air and wood temperature of less than 5°C and greater than +30°C.

5 to 10 m²/l.

50% relative humidity):

After rinsing, allow the wood to dry for 3 days before applying

Safety: Refer to the safety date sheet and the text given on the packaging, in accordance with the applicable legislation.

he information set out cons are purely illustrative and are not the responsibility of the manufacturer, the application of products not made under his supervisior



Recommendations before application

- Shake the product well before use.
- Ready to use.
- Wear rubber gloves, protective glasses.
- Protect parts that are not to be treated, particularly aluminium parts.
- Do not apply at an ambient air and wood temperature of less than +5°C and greater than +30°C.

Directions for use

- Always wet the surface with clean fresh water before application.
- Apply Wood Cleaner to the entire surface with a brush or synthetic roller (long hair).
- Scrub the parts to be cleaned with a hard bristle nylon brush.
- Allow to act for around 15 minutes.
- Scrub surface while rinsing with lots of water or use a pressure washer (max. 60 bar).
- Repeat the operation if necessary.

Advice of the professionals

If grey is not eliminated entirely this means that protection type teak oil, linseed or other has been applied previously. In this case, apply the system Wood Oil Cleaner* + Wood Cleaner.

* same manufacturer



Durieu S.A. 91070 BONDOUFLE - France T. +33 (0)1 60 86 48 70 F. +33 (0)1 60 86 84 84 info@durieu.com www.durieu.com

Durieu Coatings S.A. / N.V. New Tech Center Avenue Albert Einstein 2 A 1348 Louvain-La-Neuve Belgique / België T. +32 (0)10 420 090 F. +32 (0)10 420 099 info@durieucoatings.com www.durieucoatings.com



www.linitop.com

For further help or advice please contact us on:

Belgium: +32 (0)10 420090 - 0800 95549

France: +33 (0)1 60 86 48 70

or consult our site: www.linitop.com

This notice cancels and replaces all previous notices on the same product. The advice provided, in particular on the maintenance, is only indicative and cannot substitute for an appropriate description of the nature and condition of the surface to be worked on. With technical developments continually occurring, it is for our customers to check, before application, with our services that this notice has not been replaced by a more recent edition.