

LINITOP®

WOOD OIL CLEANER



EXTERIOR



priority to wood

Description

Deep removal of teak and linseed oils darkened by UV. Restores the original appearance to the wood. Gelified water-based product.

Properties

- Fast acting - works in 5 minutes. Rinse with water.
- Makes the oils water soluble.
- Also removes different stains from composite woods.
- Opens the pores of tropical hardwoods - removes mill glaze.
- Ready to use.
- No solvents or paraffin. Biodegradable.
- Requires neutralisation with Wood Cleaner**.

Basic uses

- Directly on outdoor resinous wood, pressure treated or otherwise, tropical hardwoods, broadleaved wood*, already protected by oils but soiled or darkened.
 - Effective on all surfaces: terraces, duckboards, weatherboarding, chalets, boat decks, garden furniture...
- * Except oak and chestnut.

Characteristics

- **Composition:** Sodium hydroxide.
- **Density (at +20°C):** 1.030 ± 0.05.
- **Flash point:** Not classified as inflammable.
- **Packaging:** 1 l - 2.5 l.
- **Shelf life:** At least 2 years in the closed original packaging.
- **Storage conditions:** Keep away from frost and high temperatures.
- **Appearance in the can:** Gel.
- **Tools:** Nylon or synthetic brushes.
- **Dilution:** Do not dilute. Ready to use.
- **Cleaning of the tools:** Water.
- **Conditions of application:** Do not apply at an ambient air and wood temperature of less than +5°C and greater than +30°C.
- **Coverage:** 3 to 5 m²/l.
- **Safety:** Refer to the safety data sheet and the text given on the packaging, in accordance with the applicable legislation.

Priority to Wood

Recommendations before application

- Shake the product well before use. Ready to use.
- Wear rubber gloves, spectacles and appropriate protection.
- Protect the parts that are not to be treated, in particular the aluminium parts.
- Do not apply at an ambient air and wood temperature of less than +5°C and greater than +30°C.

Directions for use

- On dry wood, apply a thick coat of Wood Oil Cleaner to the surface to be cleaned.
- Allow the product to work for a maximum of 5 minutes.
- Scrub surface with stiff nylon brush and rinse thoroughly or use a pressure washer (max 50 bar).
- After rinsing and while wood is still wet, immediately neutralise surface with Wood Cleaner**.

Advice of the professionals

When the surface to be cleaned is large, work in small areas, so that the product is not in contact with the surface for more than 5 minutes.

If possible, the use of hot water for rinsing with makes the removal of the oils easier.

Neutralisation with Wood Cleaner** is not required after removing the stains from composite wood. A good rinse is sufficient.

** same manufacturer

LINITOP® is a trademark



Durieu S.A.
91070 BONDOUFLE - France
T. +33 (0)1 60 86 48 70
F. +33 (0)1 60 86 84 84
info@durieu.com
www.durieu.com

Durieu Coatings S.A. / N.V.
New Tech Center
Avenue Albert Einstein 2 A
1348 Louvain-La-Neuve
Belgique / België
T. +32 (0)10 420 090
F. +32 (0)10 420 099
info@durieucoatings.com
www.durieucoatings.com

0800 95 549

For further help or advice please contact us on:
Belgium: +32 (0)10 420090 - 0800 95549
France: +33 (0)1 60 86 48 70
or consult our site: www.linitop.com